NSN 5962-00-493-6566

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-493-6566 **Body Length:** 0.395 inches **Body Width:** 0.395 inches **Body Height:** Between 0.035 inches and 0.075 inches **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and negative outputs and high current **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 4 switch **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 6.0 volts power source **Time Rating Per Chacteristic:** 250.00 nanoseconds propagation delay time, low to high level output and 140.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 17863-7104051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli