

View Online at <https://aerobasegroup.com/nsn/5962-00-493-6605>

**Body Length:**

Between 0.660 inches and 0.785 inches

**Body Width:**

Between 0.220 inches and 0.280 inches

**Body Height:**

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:**

220.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and positive outputs and high speed and w/enable and asynchronous and negative edge triggered and w/clear

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 4 input

**Design Function And Quantity:**

2 flip-flop, clocked and 2 flip-flop, j-k, master slave

**Case Outline Source And Designator:**

T0-116 joint electron device engineering council

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

30.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold and body gold

**Precious Material:**

Gold

**Test Data Document:**

49956-465701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0