NSN 5962-00-496-2209



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-496-2209 **Body Length:** Between 0.750 inches and 0.895 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.120 inches and 0.180 inches **Maximum Power Dissipation Rating:** 100.0 milliwatts **Operating Tempurature Range:** -30.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and high speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Emitter-coupled logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nor **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -8.0 volts power source and 0.0 volts power source **Time Rating Per Chacteristic:** 3.70 nanoseconds propagation delay time, low to high level output and 3.70 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0