# NSN 5962-00-496-2209

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-496-2209

## **Body Length:**

Between 0.750 inches and 0.895 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

## **Body Height:**

Between 0.120 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

100.0 milliwatts

## **Operating Tempurature Range:**

-30.0/+85.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Monolithic and hermetically sealed and negative outputs and high speed

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

## **Output Logic Form:**

Emitter-coupled logic

## Input Circuit Pattern:

Quad 2 input

## **Design Function And Quantity:**

4 gate, nor

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-8.0 volts power source and 0.0 volts power source

## Time Rating Per Chacteristic:

3.70 nanoseconds propagation delay time, low to high level output and 3.70 nanoseconds propagation delay time, high to low level output

## Terminal Type And Quantity:

16 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0