NSN 5962-00-497-3905



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-00-497-3905 **Body Length:** Between 0.919 inches and 1.000 inches **Body Width:** 0.922 inches **Body Height:** 0.146 inches **Maximum Power Dissipation Rating:** 250.0 milliwatts **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+135.0 degrees celsius **Features Provided:** Hermetically sealed and hybrid and positive outputs and high speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Single-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 counter, binary **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 6.0 volts power source **Time Rating Per Chacteristic:** 5.00 nanoseconds propagation delay time, low to high level output and 5.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold

Test Data Document:

13499-351-7070 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

15 pin

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5962-00-497-3905

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0