Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-497-9278

Body Length:	
0.250 inches	
Body Width:	
0.125 inches	
Body Height:	
0.055 inches	
Maximum Power Dis	sipation Rating:
63.0 milliwatts	
Operating Tempurat	ure Range:
-55.0/+125.0 degrees	celsius
Storage Tempuratur	e Range:
-65.0/+150.0 degrees	celsius
Features Provided:	
Hermetically sealed a	nd monolithic and positive outputs and gated output
Inclosure Material:	
Ceramic and glass	
Inclosure Configurat	ion:
Flat pack	
Output Logic Form:	
Diode-transistor logic	
Input Circuit Pattern	:
Quad 1 input	
Design Function And	d Quantity:
6 inverter	
Terminal Surface Tre	eatment:
Gold	
Voltage Rating And	Type Per Characteristic:
10.0 volts power sour	ce
Time Rating Per Cha	icteristic:
30.00 nanoseconds p	propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output	
Precious Material Ar	nd Location:
Terminal surface gold	
Precious Material:	
Gold	
Test Data Document	:
13499-351-7256 spec	ification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes com	mercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	rformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And (
14 flat leads	
Shelf Life:	

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-00-497-9278

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

