NSN 5962-00-498-2689

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-498-2689

Body Length:	
0.250 inches	
Body Width:	
0.250 inches	
Body Height:	
0.070 inches	
Maximum Power Dissipation Rating:	
500.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and burn in and w/clock and w/resistor	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Flat pack	
Output Logic Form:	
Diode-transistor logic	
Input Circuit Pattern:	
Dual 4 input	
Design Function And Quantity:	
2 flip-flop, j-k, clocked	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
8.0 volts power source	
Time Rating Per Chacteristic:	
75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time,	high to low level
output	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).	
Terminal Type And Quantity:	
14 flat leads	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	