# NSN 5962-00-503-9841

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-503-9841

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

#### **Body Height:**

Between 0.165 inches and 0.185 inches

# **Maximum Power Dissipation Rating:**

300.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and adjustable and positive outputs

#### **Inclosure Material:**

Glass and metal

#### **Inclosure Configuration:**

# Can

**Input Circuit Pattern:** 

5 input

#### **Design Function And Quantity:**

1 amplifier, general purpose

#### **Case Outline Source And Designator:**

T0-99 joint electron device engineering council

# **Terminal Surface Treatment:**

Gold

### Voltage Rating And Type Per Characteristic:

6.0 volts input

#### **Precious Material And Location:**

Terminal surface gold

#### **Precious Material:**

Gold

# **Test Data Document:**

13499-351-1011 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

8 pin

Shelf Life:

N/a

# Unit Of Measure:

#### **Demilitarization:**

Yes - demil/mli

Fiig:

A458a0