## NSN 5962-00-515-2270

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-515-2270
Body Length:
Between 0.740 inches and 0.780 inches
Body Width:
Between 0.282 inches and 0.313 inches
Body Height:
Between 0.135 inches and 0.165 inches
Maximum Power Dissipation Rating:
750.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 phase locked loop
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
26.0 volts power source
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
97384-5339-090619 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0