NSN 5962-00-515-3226



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-515-3226 **Body Length:** 2.010 inches **Body Width:** 1.010 inches **Body Height:** Between 0.370 inches and 0.415 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and adjustable and temperature controlled and positive outputs and high gain **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 switch, analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 150.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 08783-37653350 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 11 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig:

Demilitarization: Yes - demil/mli