## NSN 5962-00-515-3601

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-515-3601

Between 0.320 inches and 0.380 inches

**Body Width:** 

Between 0.240 inches and 0.270 inches

**Body Height:** 

Between 0.050 inches and 0.080 inches

**Maximum Power Dissipation Rating:** 

800.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and bipolar and programmable and programmed and w/buffered output and w/decoded output and w/open collector and w/enable and w/storage

#### **Inclosure Material:**

Ceramic and glass

## **Inclosure Configuration:**

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

## **Input Circuit Pattern:**

14 input

## **Terminal Surface Treatment:**

Solder

## **Voltage Rating And Type Per Characteristic:**

5.5 volts power source

#### **Time Rating Per Chacteristic:**

70.00 nanoseconds propagation delay time, low to high level output and 175.00 nanoseconds propagation delay time, high to low level output

## **Memory Device Type:**

Rom

#### **Memory Capacity:**

Unknown

#### **Test Data Document:**

99971-7537180 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

24 flat leads

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

Vec - demil/mli

# **NSN 5962-00-515-3601** Memory Microcircuit - Page 2 of 2



Fiig:

A458a0