NSN 5962-00-517-7724



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-517-7724 **Body Length:** 0.640 inches **Body Width:** 0.640 inches **Body Height:** 0.135 inches **Maximum Power Dissipation Rating:** 125.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and hybrid and positive outputs and adjustable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 1 amplifier, hybrid **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Time Rating Per Chacteristic:** 350.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 03640-6088707 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 22 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0