Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-517-7724

Body Length:
0.640 inches
Body Width:
0.640 inches
Body Height:
0.135 inches
Maximum Power Dissipation Rating:
125.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs and hybrid and positive outputs and adjustable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
10 input
Design Function And Quantity:
1 amplifier, hybrid
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
350.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
03640-6088707 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format

03640-6088707 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

22 flat leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0