## NSN 5962-00-520-4406

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-520-4406 **Overall Width:** Between 0.600 inches and 1.000 inches **Body Length:** 0.400 inches **Body Width:** Between 0.200 inches and 0.300 inches **Body Height:** Between 0.008 inches and 0.100 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Medium speed and low impedance and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Triple 3 input **Design Function And Quantity:** 3 gate, nand **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 15.0 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 14 flat leads **Specification Data:** 25500-3100109-007 manufacturers source control Shelf Life: N/a

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

## NSN 5962-00-520-4406

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0