NSN 5962-00-521-1974

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-521-1974
Body Length:
Between 0.990 inches and 1.035 inches
Body Width:
Between 0.745 inches and 0.825 inches
Body Height:
Between 0.100 inches and 0.165 inches
Maximum Power Dissipation Rating:
2.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 switch, current and 2 switch, voltage
Terminal Surface Treatment:
Tin
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
22915-2-040 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
32 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Ves - demil/mli

Fiig:

A458a0