NSN 5962-00-521-2062



Memory Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-521-2062 **Body Outside Diameter:** 0.556 inches **Maximum Power Dissipation Rating:** 150.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Can **Output Logic Form:** Metal oxide-semiconductor logic **Terminal Surface Treatment:** Gold **Product Name:** Data detection timing a array **Voltage Rating And Type Per Characteristic:** 0.3 volts power source **Memory Device Type:** Pal **Precious Material And Location:** Case cover and bottom gold **Precious Material:** Gold **Test Data Document:** 13499-351-8049 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 34 flat leads Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0