NSN 5962-00-521-2144

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-521-2144 **Body Length:** Between 0.210 inches and 0.270 inches **Body Width:** Between 0.330 inches and 0.355 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 150.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs **Inclosure Material:** Glass and metal **Inclosure Configuration:** Flat pack **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 buffer, noninverting **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** -15.0 volts power source and 0.3 volts power source **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 13499-351-8024 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5962-00-521-2144Digital Microcircuit - Page 2 of 2



Fiig:

A458a0