NSN 5962-00-522-7903

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-522-7903

Body Length:

Between 1.424 inches and 1.456 inches

Body Width:

Between 0.859 inches and 0.891 inches

Body Height:

Between 0.824 inches and 0.856 inches

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Asynchronous and synchronous and w/enable and resettable

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 4 input

Design Function And Quantity:

4 flip-flop, j-k, clocked

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Chacteristic:

75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

88818-c528000506 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

26 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-00-522-7903 Digital Microcircuit - Page 2 of 2

Fiig: A458a0

