## NSN 5962-00-528-1315

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-528-1315

Between 0.660 inches and 0.785 inches  Body Width:  Between 0.220 inches and 0.280 inches  Body Height:  Between 0.140 inches and 0.180 inches  Maximum Power Dissipation Rating: 217.0 milliwatts  Operating Tempurature Range: -55.04+125.0 degrees celsius  Storage Tempurature Range: -65.04+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawling (this is the basic governing drawling, such as a contractor drawling, original equipment manufacturer drawling, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawling)  Sheff Life:  N/a  Unit Of Measure: Demilitarization: Yes - demil/mil  Flig:	
Between 0.220 inches and 0.280 inches Between 0.220 inches and 0.280 inches Bedween 0.140 inches and 0.180 inches Maximum Power Dissipation Rating: 217.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Dosign Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Domilitarization: Yes - demill/mil	Body Length:
Between 0.220 inches and 0.280 inches  Body Height:  Between 0.140 inches and 0.180 inches  Maximum Power Dissipation Rating:  217.0 millivatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and positive outputs  Inclosure Material: Ceramic and glass  Inclosure Configuration: Dual-in-line  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter  Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 99956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: Na Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	Between 0.660 inches and 0.785 inches
Bottween 0.140 inches and 0.180 inches Maximum Power Dissipation Rating: 217.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Onfiguration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Body Width:
Between 0.140 inches and 0.180 inches  Maximum Power Dissipation Rating: 217.0 milliwatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	Between 0.220 inches and 0.280 inches
Maximum Power Dissipation Rating: 217.0 milliwaits Operating Tempurature Range: -55.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Ontiguration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Dosign Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit of Measure: Demilitarization: Yes - demil/mili Flig:	Body Height:
217.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: To-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mil Fiig:	Between 0.140 inches and 0.180 inches
Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mili Flig:	Maximum Power Dissipation Rating:
-55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	217.0 milliwatts
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Operating Tempurature Range:
Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	-55.0/+125.0 degrees celsius
Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	Storage Tempurature Range:
Hermetically sealed and monolithic and positive outputs  Inclosure Material: Ceramic and glass  Inclosure Configuration: Dual-in-line  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	-65.0/+150.0 degrees celsius
Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Features Provided:
Ceramic and glass Inclosure Configuration:  Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Hex 1 input Design Function And Quantity: 6 inverter Case Outline Source And Designator: T0-116 joint electron device engineering council Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Hermetically sealed and monolithic and positive outputs
Inclosure Configuration:  Dual-in-line  Output Logic Form:  Transistor-transistor logic  Input Circuit Pattern:  Hex 1 input  Design Function And Quantity: 6 inverter  Case Outline Source And Designator:  T0-116 joint electron device engineering council  Test Data Document:  49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Inclosure Material:
Dual-in-line  Output Logic Form: Transistor-transistor logic  Input Circuit Pattern: Hex 1 input  Design Function And Quantity: 6 inverter  Case Outline Source And Designator: T0-116 joint electron device engineering council  Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli  Fitig:	Ceramic and glass
Output Logic Form:  Transistor-transistor logic  Input Circuit Pattern:  Hex 1 input  Design Function And Quantity: 6 inverter  Case Outline Source And Designator:  T0-116 joint electron device engineering council  Test Data Document:  49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fitig:	Inclosure Configuration:
Transistor-transistor logic  Input Circuit Pattern:  Hex 1 input  Design Function And Quantity: 6 inverter  Case Outline Source And Designator:  T0-116 joint electron device engineering council  Test Data Document:  49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fitig:	Dual-in-line Dual-in-line
Input Circuit Pattern: Hex 1 input  Design Function And Quantity: 6 inverter  Case Outline Source And Designator: T0-116 joint electron device engineering council  Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli  Fitig:	Output Logic Form:
Hex 1 input  Design Function And Quantity: 6 inverter  Case Outline Source And Designator: T0-116 joint electron device engineering council  Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli  Fitig:	Transistor-transistor logic
Design Function And Quantity: 6 inverter  Case Outline Source And Designator: T0-116 joint electron device engineering council  Test Data Document: 49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli  Fiig:	Input Circuit Pattern:
6 inverter  Case Outline Source And Designator:  T0-116 joint electron device engineering council  Test Data Document:  49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Hex 1 input
Case Outline Source And Designator:  T0-116 joint electron device engineering council  Test Data Document:  49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Design Function And Quantity:
T0-116 joint electron device engineering council  Test Data Document:  49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	6 inverter
Test Data Document:  49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Case Outline Source And Designator:
49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	T0-116 joint electron device engineering council
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	49956-480829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Filg:	Unit Of Measure:
Yes - demil/mli Filg:	
Fiig:	Demilitarization:
	Yes - demil/mli
A458a0	Fiig:
	A458a0