NSN 5962-00-530-4652

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-530-4652

Body Length:

Between 0.370 inches and 0.409 inches

Body Width:

Between 0.249 inches and 0.283 inches

Body Height:

0.075 inches

Maximum Power Dissipation Rating:

160.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and w/open collector and positive outputs

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

1 multiplexer

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Chacteristic:

38.00 nanoseconds propagation delay time, low to high level output and 38.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal and body surfaces gold

Precious Material:

Gold

Test Data Document:

94117-310172 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5962-00-530-4652

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

