NSN 5962-00-530-4694

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-530-4694

Body Length:

Between 0.235 inches and 0.385 inches

Body Width:

Between 0.140 inches and 0.260 inches

Body Height:

0.070 inches

Maximum Power Dissipation Rating:

70.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and expandable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

3 wide 3 input

Design Function And Quantity:

1 gate, and-nor

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Chacteristic:

6.00 nanoseconds propagation delay time, low to high level output and 6.00 nanoseconds propagation delay time, high to low level output

Special Features:

Formed leads

Test Data Document:

94117-310151 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

- ---
- Demilitarization:
- Yes demil/mli

NSN 5962-00-530-4694 Digital Microcircuit - Page 2 of 2

Fiig: A458a0

