NSN 5962-00-531-7738

Digital Microcircuit - Page 1 of 1

1 multivibrator, monostable

Time Rating Per Chacteristic:

Precious Material And Location:

output

Gold

N/a

Fiig: A458a0

Shelf Life:

Unit Of Measure:

Demilitarization: Yes - demil/mli

Terminals gold

Precious Material:

Case Outline Source And Designator:

T0-86 joint electron device engineering council



View Online at https://aerobasegroup.com/nsn/5962-00-531-7738 **Body Length:** Between 0.240 inches and 0.275 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 125.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and retriggerable and high speed and complementary outputs and edge triggered and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:**

40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level