NSN 5962-00-531-7781

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-531-7781

| View Online at https://aerobasegroup.com/nsn/5962-00-531-7781 |
|---|
| Body Length: |
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 80.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+75.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Features Provided: |
| Monolithic and negative outputs and high speed and internally compensated and wire-or outputs |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Emitter-coupled logic |
| Input Circuit Pattern: |
| 6 input |
| Design Function And Quantity: |
| 1 gate, and-nand and 1 gate, or-nor |
| Case Outline Source And Designator: |
| T0-116 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 0.0 volts power source |
| Time Rating Per Chacteristic: |
| 4.00 nanoseconds propagation delay time, low to high level output |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0