## NSN 5962-00-532-1023

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-532-1023 **Body Length:** Between 0.240 inches and 0.275 inches **Body Width:** Between 0.160 inches and 0.185 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 264.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and high speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Hex 1 input **Design Function And Quantity:** 6 inverter, digital **Case Outline Source And Designator:** T0-85 joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Special Features:** Formed leads **Test Data Document:** 94117-310144 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;

excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

14 flat leads

Shelf Life:

N/a

**Unit Of Measure:** 

--

## **Demilitarization:**

Yes - demil/mli

## **NSN 5962-00-532-1023**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0