## NSN 5962-00-534-7023



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-534-7023 **Body Length:** Between 0.240 inches and 0.260 inches **Body Width:** Between 0.140 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Special Features:** Formed leads **Test Data Document:** 94117-310058 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:** 

## --

Demilitarization:

Yes - demil/mli

Fiig:

A458a0