# NSN 5962-00-534-7242

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-534-7242

### **Body Length:**

Between 0.660 inches and 0.790 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

0.185 inches

#### **Maximum Power Dissipation Rating:**

132.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

### **Output Logic Form:**

Transistor-transistor logic

### Input Circuit Pattern:

Hex 1 input

### **Design Function And Quantity:**

6 inverter

### **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

5.5 volts power source

### Time Rating Per Chacteristic:

18.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

94117-310173 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

### Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig: