

View Online at <https://aerobasegroup.com/nsn/5962-00-534-7276>

**Body Length:**

1.970 inches

**Body Width:**

0.500 inches

**Body Height:**

0.090 inches

**Maximum Power Dissipation Rating:**

600.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-55.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and expandable and programmable and programmed and synchronous and w/enable and positive outputs

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

P-type metal oxide-semiconductor logic

**Input Circuit Pattern:**

26 input

**Design Function And Quantity:**

1 multiplexer

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

0.3 volts power source

**Time Rating Per Characteristic:**

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

94117-310196 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

40 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

Fig: