NSN 5962-00-534-7276

Digital Microcircuit - Page 1 of 1

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-00-534-7276

Body Length:
1.970 inches
Body Width:
0.500 inches
Body Height:
0.090 inches
Maximum Power Dissipation Rating:
600.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and expandable and programmable and programmed and synchronous and w/enable and positive
outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
P-type metal oxide-semiconductor logic
Input Circuit Pattern:
26 input
Design Function And Quantity:
1 multiplexer
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
0.3 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
94117-310196 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
40 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: