# NSN 5962-00-539-0683

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-539-0683

## **Body Length:**

Between 0.755 inches and 0.785 inches

## **Body Width:**

Between 0.245 inches and 0.280 inches

## **Body Height:**

0.180 inches

### **Maximum Power Dissipation Rating:**

240.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs

#### **Inclosure Material:**

# Ceramic and glass

Inclosure Configuration:

Dual-in-line

### **Output Logic Form:**

Transistor-transistor logic

### Input Circuit Pattern:

Quad 2 input

### **Design Function And Quantity:**

4 gate, nor

### **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

5.5 volts power source

### Time Rating Per Chacteristic:

22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

81413-226562 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

# Fiig:

A458a0