NSN 5962-00-539-4156

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-539-4156 **Body Length:** Between 0.240 inches and 0.260 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.050 inches and 0.065 inches **Maximum Power Dissipation Rating:** 44.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and high speed and medium power and positive outputs and expandable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 2 wide 2 input **Design Function And Quantity:** 2 gate, and-or invert **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 5.5 volts power source **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 35351-151462 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-00-539-4156Digital Microcircuit - Page 2 of 2



Fiig:

A458a0