NSN 5962-00-548-1629

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-548-1629

Body Length:	
0.785 inches	
Body Width:	
0.280 inches	
Body Height:	
0.155 inches	
Maximum Power Dissipation Rating:	
32.5 milliwatts	
Operating Tempurature Range:	
-25.0/+75.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Monolithic and hermetically sealed and positive outputs and expandable and low power	
Inclosure Material:	
Ceramic and glass	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Diode-transistor logic	
Input Circuit Pattern:	
Dual 5 input	
Design Function And Quantity:	
2 gate, nand-nor	
Time Rating Per Chacteristic:	
80.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low	level
output	
Precious Material And Location:	
Terminal surface gold	
Precious Material:	
Gold	
Test Data Document:	
07187-2501557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing	ing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

Yes - demil/mli

Fiig:

A458a0