

View Online at <https://aerobasegroup.com/nsn/5962-00-548-1634>

**Body Length:**

0.785 inches

**Body Width:**

0.280 inches

**Body Height:**

0.155 inches

**Maximum Power Dissipation Rating:**

32.5 milliwatts

**Operating Temperature Range:**

-25.0/+75.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and positive outputs and expandable and low power

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Diode-transistor logic

**Input Circuit Pattern:**

Dual 5 input

**Design Function And Quantity:**

2 gate, nand-nor

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

80.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminal surface gold

**Precious Material:**

Gold

**Test Data Document:**

07187-2501557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0