NSN 5962-00-551-9478

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-551-9478 **Body Length:** 0.260 inches **Body Width:** 0.280 inches **Body Height:** 0.070 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 comparator, voltage, differential **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 15.0 volts power source **Time Rating Per Chacteristic:** 200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932180 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli Fiig:

Demilitarization:

A458a0