NSN 5962-00-556-6158

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-556-6158

| Body Outside Diameter: |
|---|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| 0.180 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| 65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic |
| nclosure Material: |
| Metal |
| nclosure Configuration: |
| Can |
| nput Circuit Pattern: |
| Dual 1 input |
| Design Function And Quantity: |
| 2 driver, line |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.0 volts power source |
| Time Rating Per Chacteristic: |
| 200.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level |
| putput |
| Test Data Document: |
| 56232-1603160 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 10 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |
| Filg: |
| A458a0 |
| |