## NSN 5962-00-563-1972

Digital Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-00-563-1972   |
|---|
| Body Length:  |
| Between 0.660 inches and 0.785 inches   |
| Body Width:   |
| Between 0.220 inches and 0.280 inches   |
| Body Height:  |
| Between 0.140 inches and 0.180 inches   |
| Maximum Power Dissipation Rating:   |
| 85.0 milliwatts   |
| Operating Tempurature Range:  |
| +0.0/+75.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and monolithic and positive outputs and low power and medium speed and resettable                               |
| Inclosure Material:   |
| Ceramic and glass   |
| Inclosure Configuration:  |
| Dual-in-line  |
| Output Logic Form:  |
| Diode-transistor logic  |
| Input Circuit Pattern:  |
| Triple 2 input  |
| Design Function And Quantity:   |
| 3 flip-flop, r-s  |
| Case Outline Source And Designator:   |
| T0-116 joint electron device engineering council  |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| 5.5 volts power source  |
| Time Rating Per Chacteristic:   |
| 25.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, low to high level  |
| output and 10.00 nanoseconds propagation delay time, high to low level output and 30.00 nanoseconds propagation delay time, high to |
| low level output  |
| Terminal Type And Quantity:   |
| 14 printed circuit  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

Fiig: A458a0

No