NSN 5962-00-570-4933

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-570-4933

Body Length:	
0.280 inches	
Body Width:	
Between 0.240 inch	es and 0.260 inches
Body Height:	
Between 0.030 inch	es and 0.085 inches
Maximum Power D	issipation Rating:
396.0 milliwatts	
Operating Tempur	ature Range:
-55.0/+125.0 degree	us celsius
Storage Tempurat	ire Range:
-65.0/+150.0 degree	es celsius
Features Provided	
Hermetically sealed	and monolithic and positive outputs and high speed and w/totem pole output
Inclosure Material	
Ceramic and glass	
Inclosure Configu	ation:
Flat pack	
Output Logic Forn	
Transistor-transisto	logic
Input Circuit Patte	n:
Dual 4 input	
Design Function A	nd Quantity:
2 gate, nand	
Case Outline Sour	ce And Designator:
F-1 mil-m-38510	
Terminal Surface	reatment:
Solder	
Voltage Rating An	d Type Per Characteristic:
18.0 volts power so	urce
Test Data Docume	nt:
81349-mil-m-38510	specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes co	mmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And	Quantity:
14 flat leads	
Specification Data	
81349-mil-m-38510	23 government specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	

NSN 5962-00-570-4933 Digital Microcircuit - Page 2 of 2

Fiig: A458a0

