NSN 5962-00-580-2922

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-580-2922

view Online at https://aerobasegroup.com/nsn/5962-00-580-2922
Body Length:
0.810 inches
Body Width:
0.294 inches
Body Height:
0.180 inches
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and w/open collector and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Terminal Surface Treatment:
Solder
Solder
Solder Voltage Rating And Type Per Characteristic:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity: 16 printed circuit
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity: 16 printed circuit Shelf Life:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure:
Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Time Rating Per Chacteristic: 100.00 nanoseconds propagation delay time, low to high level output Memory Device Type: Rom Memory Capacity: Unknown Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli