NSN 5962-00-581-7780

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-581-7780

| Body Length: | |
|--|-----------|
| 0.395 inches | |
| Body Width: | |
| 0.290 inches | |
| Body Height: | |
| 0.080 inches | |
| Maximum Power Dissipation Rating: | |
| 60.0 milliwatts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| End Application: | |
| Type f-tf-15a aircraft | |
| Features Provided: | |
| Hybrid and hermetically sealed and positive outputs | |
| Inclosure Material: | |
| Ceramic and glass | |
| Inclosure Configuration: | |
| Flat pack | |
| Input Circuit Pattern: | |
| Dual 2 input | |
| Design Function And Quantity: | |
| 2 switch, analog | |
| Terminal Surface Treatment: | |
| Solder | |
| Voltage Rating And Type Per Characteristic: | |
| -10.0 volts power source and 5.0 volts power source | |
| Time Rating Per Chacteristic: | |
| 30.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to | low level |
| output | |
| Terminal Type And Quantity: | |
| 14 flat leads | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| A458a0 | |
| | |