

View Online at <https://aerobasegroup.com/nsn/5962-00-584-1646>

Body Length:

Between 0.665 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Type an/tcc-78 multiplexer set

Features Provided:

Monolithic and hermetically sealed and low power and high gain and negative outputs and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 2 input

Case Outline Source And Designator:

T0-116 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Characteristic:

800.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Rom

Test Data Document:

80063-sm-a-732441 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

15 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0