NSN 5962-00-595-8504

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-595-8504

| | ps.//aerobasegroup.com/msr//3902-00-395-6504 |
|------------------------------|--|
| Body Length: | |
| 0.896 inches | |
| Body Width: | |
| Between 0.220 in | ches and 0.310 inches |
| Body Height: | |
| Between 0.140 in | ches and 0.185 inches |
| Maximum Power | Dissipation Rating: |
| 280.0 milliwatts | |
| Operating Temp | urature Range: |
| -55.0/+125.0 degi | rees celsius |
| Storage Tempura | ature Range: |
| -65.0/+150.0 degi | rees celsius |
| Features Provide | ed: |
| Hermetically seale | ed and monolithic and positive outputs and w/enable and complementary outputs |
| Inclosure Materia | al: |
| Ceramic and glas | S |
| Inclosure Config | uration: |
| Dual-in-line | |
| Output Logic Fo | rm: |
| Transistor-transis | tor logic |
| Input Circuit Pat | tern: |
| 6 input | |
| Design Function | And Quantity: |
| 1 latch, d | |
| Case Outline So | urce And Designator: |
| D-2 mil-m-38510 | |
| Terminal Surface | e Treatment: |
| Solder | |
| Voltage Rating A | nd Type Per Characteristic: |
| -0.5 volts powers | source and 7.0 volts power source |
| Test Data Docun | nent: |
| 81349-mil-m-385 ² | 0 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes | commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and | d performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type A | nd Quantity: |
| 16 printed circuit | |
| Specification Da | ta: |
| 81349-mil-m-385 ² | 10/15 government specification |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |

NSN 5962-00-595-8504 Digital Microcircuit - Page 2 of 2

Fiig: A458a0

