NSN 5962-00-615-6101

Linear Microcircuit - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-00-615-6101

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Radar set type an/fps-110
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and internally compensated
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
36.0 volts total supply
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

NSN 5962-00-615-6101 Linear Microcircuit - Page 2 of 2



Fiig:

A458a0