NSN 5962-00-624-8673



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-00-624-8673 **Body Length:** 0.873 inches **Body Width:** 0.513 inches **Body Height:** 0.275 inches **Maximum Power Dissipation Rating:** 2.5 watts **Operating Tempurature Range:** -20.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs **Inclosure Material:** Glass and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 regulator, voltage **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output **Special Features:** Trip point voltage 5.0v dc **Precious Material And Location:** Body surface gold **Precious Material:** Gold **Test Data Document:** 26512-g-820nk drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life:

N/a

Unit Of Measure:

NSN 5962-00-624-8673

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0