## NSN 5962-00-628-6183

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-628-6183

## **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

## **Body Height:**

Between 0.165 inches and 0.185 inches

## Maximum Power Dissipation Rating:

300.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Flight simulator type f-15a

## **Features Provided:**

Monolithic and hermetically sealed and negative outputs and positive outputs and w/chopper

#### Inclosure Material:

## Glass and metal

## Inclosure Configuration:

Can

#### **Input Circuit Pattern:**

2 input

## **Design Function And Quantity:**

1 amplifier, operational, general purpose

## Case Outline Source And Designator:

T0-99 joint electron device engineering council

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

21.0 volts power source

## Time Rating Per Chacteristic:

200.00 nanoseconds propagation delay time, low to high level output

## Precious Material And Location:

Terminals gold

#### **Precious Material:**

Gold

## **Terminal Type And Quantity:**

8 pin

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

# NSN 5962-00-628-6183

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

