# NSN 5962-00-632-8249

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-632-8249

# **Body Length:**

Between 0.660 inches and 0.785 inches

### **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

# **Maximum Power Dissipation Rating:**

22.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Unit p/n 31-038672-01

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and schottky and w/totem pole output

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

### **Output Logic Form:**

Transistor-transistor logic

# Input Circuit Pattern:

Quad 2 input

#### **Design Function And Quantity:**

4 gate, nor

#### **Case Outline Source And Designator:**

T0-116 joint electron device engineering council

#### Time Rating Per Chacteristic:

20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

#### . . . . .

# Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0