

View Online at <https://aerobasegroup.com/nsn/5962-00-659-6928>

Body Length:

Between 0.750 inches and 0.895 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

200.0 milliwatts

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

2m/mtr piece parts - shore ima

Features Provided:

Hermetically sealed and monolithic and w/enable and negative outputs and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

P-type metal oxide-semiconductor logic

Input Circuit Pattern:

8 channel

Design Function And Quantity:

1 multiplexer

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-35.0 volts power source and 0.3 volts power source

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

17773-11361953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0