## NSN 5962-00-689-8760

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-689-8760

| Body Outside Diameter:  |
|---|
| Between 0.305 inches and 0.335 inches   |
| Body Height:  |
| Between 0.160 inches and 0.185 inches   |
| Operating Tempurature Range:  |
| 55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:  |
| 65.0/+150.0 degrees celsius   |
| Features Provided:  |
| Hermetically sealed and monolithic and positive outputs   |
| nclosure Material:  |
| Glass and metal   |
| nclosure Configuration:   |
| Can   |
| nput Circuit Pattern:   |
| Dual 3 input  |
| Design Function And Quantity:   |
| 2 driver  |
| Ferminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| 10.0 volts power source   |
| Fime Rating Per Chacteristic:   |
| 110.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level |
| putput  |
| Ferminal Type And Quantity:   |
| 14 pin  |
| Shelf Life:   |
| N/a   |
| Jnit Of Measure:  |
| -   |
| Demilitarization:   |
| Yes - demil/mli   |
| Filg:   |
| A458a0  |
|   |
|   |