NSN 5962-00-721-3930

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-721-3930

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and negative outputs and darlington-connected and externally compensated
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
2000.00 nanoseconds propagation delay time, low to high level output
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A 450-0

A458a0