## NSN 5962-00-734-6140

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-734-6140

The state of the s
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
62.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Darlington-connected and monolithic and positive outputs and w/totem pole output and low power and high speed
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 gate, nand
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
13.00 nanoseconds propagation delay time, low to high level output and 13.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Vas - damil/mli

**Fiig:** A458a0