# NSN 5962-00-738-7727

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-738-7727

### **Body Length:**

Between 0.770 inches and 0.790 inches

# Body Width:

Between 0.375 inches and 0.385 inches

# **Body Height:**

Between 0.052 inches and 0.062 inches

## **Maximum Power Dissipation Rating:**

625.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/enable and programmable and programmed and w/decoded output

#### **Inclosure Material:**

# Ceramic and glass

# Inclosure Configuration:

Flat pack

### **Output Logic Form:**

Transistor-transistor logic

### Input Circuit Pattern:

18 input

#### **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

### **Time Rating Per Chacteristic:**

60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output

### Memory Device Type:

Rom

#### Memory Capacity:

Unknown

#### Test Data Document:

06840-6088465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

28 flat leads

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

# NSN 5962-00-738-7727

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

