NSN 5962-00-741-2037

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-741-2037
Body Length:
Between 0.335 inches and 0.350 inches
Body Width:
Between 0.235 inches and 0.265 inches
Body Height:
Between 0.050 inches and 0.080 inches
Maximum Power Dissipation Rating:
31.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Complementary-logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nand
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
6.0 volts power source
Time Rating Per Chacteristic:
13.00 nanoseconds propagation delay time, low to high level output and 13.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
10236-7100031 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A458a0

Yes - demil/mli